

# Concepțe fundamentale ale limbajelor de programare

Programarea funcțională în practică

Curs 13

conf. dr. ing. Ciprian-Bogdan Chirila

Universitatea Politehnica Timișoara  
Departamentul de Calculatoare și Tehnologia Informației

29 mai 2023



## Cuprins

- 1 Avoiding flow control
  - 2 Comprehensions
  - 3 Generators
  - 4 Dictionaries and sets comprehensions
  - 5 Recursion
  - 6 Eliminating loops
  - 7 Streams
    - Stream creation
    - Stream operations
  - 8 Bibliography



## Avoiding flow control

- a block of code contains:
    - outside loops like for or while
    - assignment of state variables within loops
    - modification of data structures
    - branch statements if, elif, else, try, except, finally
  - it seems natural and easy
  - problems with side effects due to state variables and mutable data structures
    - a mutable object **can** be changed after its creation
    - an immutable object **cannot** be changed after its creation



# Avoiding flow control

- the problem
  - it difficult to reason accurately about what state data is in at a given point in a program
- the solution
  - is not to focus on the data construction
  - but on describing what the data collection consists of
- imperative flow control is about the "how" rather than the "what"
- to focus on "what" by refactoring the code
- to push the data construction in a more isolated place

# Encapsulation

```
# configure the data to start with
collection = get_initial_state()
state_var = None
for datum in data_set:
    if condition(state_var):
        state_var = calculate_from(datum)
        new = modify(datum, state_var)
        collection.add_to(new)
    else:
        new = modify_differently(datum)
        collection.add_to(new)

# Now actually work with the data
for thing in collection:
    process(thing)
```



# Encapsulation

```
# tuck away construction of data
def make_collection(data_set):
    collection = get_initial_state()
    state_var = None
    for datum in data_set:
        if condition(state_var):
            state_var = calculate_from(datum, state_var)
            new = modify(datum, state_var)
            collection.add_to(new)
        else:
            new = modify_differently(datum)
            collection.add_to(new)
    return collection

# Now actually work with the data
for thing in make_collection(data_set):
    process(thing)
```



## Encapsulation

- there is no program logic change
  - we shifted from **how** do we construct the collection
  - to **what** does `make_collection()` create



# Cuprins

- 1 Avoiding flow control
- 2 Comprehensions
- 3 Generators
- 4 Dictionaries and sets comprehensions
- 5 Recursion
- 6 Eliminating loops
- 7 Streams
  - Stream creation
  - Stream operations
- 8 Bibliography



# Comprehensions

- are a way to make the code more compact
- they shift the focus from **how** to **what**
- are expressions that use the same keywords as loop and conditional blocks
- inverts their order to focus on the data rather than on the procedure
- changing the form of the expression makes a large difference in how we reason about the code

# Comprehensions

```
collection = list()
for datum in data_set:
    if condition(datum):
        collection.append(datum)
    else:
        new = modify(datum)
        collection.append(new)
---
collection = [d if condition(d) else modify(d)
             for d in data_set]
```

# Comprehensions

- we saved a few characters and lines :)
- we did a mental shifting by thinking what a collection is
- we avoided to think about the state of collection in the loop
- in Python there are several types of comprehensions
  - generator comprehensions;
  - set comprehensions;
  - dict comprehensions.
- as caveat nesting comprehensions may stop clarifying and start obscuring
- the solution is to refactor into functions



# Cuprins

- 1 Avoiding flow control
- 2 Comprehensions
- 3 Generators
- 4 Dictionaries and sets comprehensions
- 5 Recursion
- 6 Eliminating loops
- 7 Streams
  - Stream creation
  - Stream operations
- 8 Bibliography



# Generator comprehensions

- have almost the same syntax as list comprehensions
- there are no square brackets around them, but parentheses
- they are also **lazy**
- they represent a description of how to get the data
- but it is not realized until one explicitly asks for it
  - by calling `.next()` on the object
  - by looping over it
- saves memory for large sequences
- defers computation until is actually needed

# Generator comprehensions

```
log_lines = (line for line in read_line(huge_log_file)
    if complex_condition(line))
---
# the imperative version
def get_log_lines(log_file):
    line = read_line(log_file)
    while True:
        try:
            if complex_condition(line):
                yield line
            line = read_line(log_file)
        except StopIteration:
            raise

log_lines = get_log_lines(huge_log_file)
```



# Generator comprehensions

```
# another imperative version
class GetLogLines(object):

    def __init__(self, log_file):
        self.log_file = log_file
        self.line = None

    def __iter__(self):
        return self

    def __next__(self):
        if self.line is None:
            self.line = read_line(log_file)
        while not complex_condition(self.line):
            self.line = read_line(self.log_file)
        return self.line

log_lines = GetLogLines(huge_log_file)
```



# Cuprins

- 1 Avoiding flow control
- 2 Comprehensions
- 3 Generators
- 4 Dictionaries and sets comprehensions
- 5 Recursion
- 6 Eliminating loops
- 7 Streams
  - Stream creation
  - Stream operations
- 8 Bibliography



## Dictionaries and sets comprehensions

```
>>> {i:chr(65+i) for i in range(6)}  
{0: 'A', 1: 'B', 2: 'C', 3: 'D', 4: 'E', 5: 'F'}  
  
>>> {chr(65+i) for i in range(6)}  
{'A', 'B', 'C', 'D', 'E', 'F'}
```



# Cuprins

- 1 Avoiding flow control
- 2 Comprehensions
- 3 Generators
- 4 Dictionaries and sets comprehensions
- 5 Recursion
- 6 Eliminating loops
- 7 Streams
  - Stream creation
  - Stream operations
- 8 Bibliography



# Recursion

- functional programming is about expressing flow control using recursion instead of loops
- thus, we can avoid altering the state of any variable within the algorithm
- recursion can be iteration having just another name
  - it is in the style of Lisp
  - it is not in the style of Python (slow at recursion and has limited stack depth `sys.setrecursionlimit(5000)` default is 1000)
- recursion can be used in solving problems by partitioning into smaller problems
- Python lacks *tail call elimination* feature



# Example of recursion being iteration

```
def running_sum(numbers, start=0):
    if len(numbers) == 0:
        print()
        return
    total = numbers[0] + start
    print(total, end=" ")
    running_sum(numbers[1:], total)
```



# Example of recursion being iteration

- this approach is not recommended
- the iteration which modifies the total state variable is more readable
- it is likely to call the function on sequences larger than 1000

# Recursion less trivial example

```
def factorialR(N):
    "Recursive factorial function"
    assert isinstance(N, int) and N >= 1
    return 1 if N <= 1 else N * factorialR(N-1)

def factorialI(N):
    "Iterative factorial function"
    assert isinstance(N, int) and N >= 1
    product = 1
    while N >= 1:
        product *= N
        N -= 1
    return product
```

# High order functions

```
from functools import reduce
from operator import mul

def factorialHOF(n):
    return reduce(mul, range(1, n+1), 1)
```

## Quicksort example

```
def quicksort(lst):
    "Quicksort over a list-like sequence"
    if len(lst) == 0:
        return lst
    pivot = lst[0]
    pivots = [x for x in lst if x == pivot]
    small = quicksort([x for x in lst if x < pivot])
    large = quicksort([x for x in lst if x > pivot])
    return small + pivots + large
```



# Cuprins

- 1 Avoiding flow control
- 2 Comprehensions
- 3 Generators
- 4 Dictionaries and sets comprehensions
- 5 Recursion
- 6 Eliminating loops
- 7 Streams
  - Stream creation
  - Stream operations
- 8 Bibliography



# Eliminating loops

- we try to eliminate all loops from a Python program
- this practice is not always desirable because it affects readability
- it is simple to apply it in a systematic manner
- if we find a function call inside a loop we can use the high order function `map()`
- there is no repeated binding of the iteration variable

## Statement and map based loop

```
for e in it: # statement-based loop
    func(e)
---
map(func, it) # map()-based "loop"
```



# Statement and map based loop

```
# let f1, f2, f3 (etc) be functions that perform actions
# an execution utility function
do_it = lambda f, *args: f(*args)

# map()-based action sequence
map(do_it, [f1, f2, f3])
```

# Using map

```
>>> hello = lambda first, last: print("Hello", first, last)
>>> bye = lambda first, last: print("Bye", first, last)
>>> _ = list(map(do_it, [hello, bye], ['David','Jane'], ['Mertz','Doe']))
Hello David Mertz
Bye Jane Doe
---
>>> do_all_funcs = lambda fns, *args: [list(map(fn, *args)) for fn in fns]
>>> _ = do_all_funcs([hello, bye],['David','Jane'], ['Mertz','Doe'])
Hello David Mertz
Hello Jane Doe
Bye David Mertz
Bye Jane Doe
```



# Eliminating loops

```
# statement-based while loop
while <cond>:
    <pre-suite>
    if <break_condition>:
        break
    else:
        <suite>
---
# FP-style recursive while loop
def while_block():
    <pre-suite>
    if <break_condition>:
        return 1
    else:
        <suite>
    return 0

while_FP = lambda: (<cond> and while_block()) or while_FP()
while_FP()
```



# Cuprins

- 1 Avoiding flow control
- 2 Comprehensions
- 3 Generators
- 4 Dictionaries and sets comprehensions
- 5 Recursion
- 6 Eliminating loops
- 7 Streams
  - Stream creation
  - Stream operations
- 8 Bibliography



# Streams

- streams are wrappers around a data source
- allow us to operate with the data source
- allows bulk processing convenient and fast
- do not store data
- are not a data structures
- do not modify the underlying data source
- `java.util.stream` present from Java 8



# Stream creation

```
private static Employee[] arrayOfEmps =  
{  
    new Employee(1, "Jeff Bezos", 100000.0),  
    new Employee(2, "Bill Gates", 200000.0),  
    new Employee(3, "Mark Zuckerberg", 300000.0)  
};  
Stream.of(arrayOfEmps);  
---  
private static List<Employee> empList = Arrays.asList(arrayOfEmps);  
empList.stream();  
---  
// streaming from individual objects  
Stream.of(arrayOfEmps[0], arrayOfEmps[1], arrayOfEmps[2]);
```

# Stream builder

```
Stream.Builder<Employee> empStreamBuilder = Stream.builder();  
  
empStreamBuilder.accept(arrayOfEmps[0]);  
empStreamBuilder.accept(arrayOfEmps[1]);  
empStreamBuilder.accept(arrayOfEmps[2]);  
  
Stream<Employee> empStream = empStreamBuilder.build();
```

# forEach operation

```
@Test
public void whenIncrementSalaryForEachEmployee_thenApplyNewSalary()
{
    empList.stream().forEach(e -> e.salaryIncrement(10.0));

    assertThat(empList, contains(
        hasProperty("salary", equalTo(110000.0)),
        hasProperty("salary", equalTo(220000.0)),
        hasProperty("salary", equalTo(330000.0))
    ));
}
```



# map operation

```
@Test
public void whenMapIdToEmployees_thenGetEmployeeStream()
{
    Integer[] empIds = { 1, 2, 3 };

    List<Employee> employees = Stream.of(empIds)
        .map(employeeRepository::findById)
        .collect(Collectors.toList());

    assertEquals(employees.size(), empIds.length);
}
```

# map operation

- produces a new stream after applying a function to each element of the original stream
- the new stream could be of different type
- in the example we converted a stream of Integers into a stream of Employees
- each Integer is passed to the function `employeeRepository::findById()`
- it returns the Employee object
- thus, it forms an Employee stream

# collect operation

```
@Test
public void whenCollectStreamToList_thenGetList()
{
    List<Employee> employees = empList.stream().collect(Collectors.toList());
    assertEquals(empList, employees);
}
```

# collect operation

- is the way to get the elements out of the stream once we are done with the processing
- performs mutable fold operations on data elements held in the Stream instance
- fold operation means repacking elements to some data structures and applying additional logic

# filter operation

```
@Test
public void whenFilterEmployees_thenGetFilteredStream()
{
    Integer[] empIds = { 1, 2, 3, 4 };

    List<Employee> employees = Stream.of(empIds)
        .map(employeeRepository::findById)
        .filter(e -> e != null)
        .filter(e -> e.getSalary() > 200000)
        .collect(Collectors.toList());

    assertEquals(Arrays.asList(arrayOfEmps[2]), employees);
}
```

# filter operation

- produces new stream of elements that passed a given test
- the test is specified by a predicate
- in the example:
  - we filtered out the *null* references for invalid employee ids
  - we filtered out the employees having salaries under a certain threshold



# findFirst operation

```
@Test
public void whenFindFirst_thenGetFirstEmployeeInStream()
{
    Integer[] empIds = { 1, 2, 3, 4 };

    Employee employee = Stream.of(empIds)
        .map(employeeRepository::findById)
        .filter(e -> e != null)
        .filter(e -> e.getSalary() > 100000)
        .findFirst()
        .orElse(null);

    assertEquals(employee.getSalary(), new Double(200000));
}
```

# findFirst operation

- return an Optional instance for the first entry in the stream
- the Optional instance may be null
- in the example:
  - we return the employee with the salary greater than a threshold
  - if no employee exists then null is returned



# toArray operation

```
@Test
public void whenStreamToArray_thenGetArray()
{
    Employee[] employees = empList.stream().toArray(Employee[]::new);
    assertThat(empList.toArray(), equalTo(employees));
}
```

# toArray operation

- we saw the example with the collection of elements
- we also can get an array out of the stream by using `toArray()` method
- in the example:
  - the `Employee[]::new` creates an empty array of Employee
  - it is then filled with elements from the stream

# flatMap operation

```
@Test
public void whenFlatMapEmployeeNames_thenGetNameStream()
{
    List<List<String>> namesNested = Arrays.asList(
        Arrays.asList("Jeff", "Bezos"),
        Arrays.asList("Bill", "Gates"),
        Arrays.asList("Mark", "Zuckerberg"));

    List<String> namesFlatStream = namesNested.stream()
        .flatMap(Collection::stream)
        .collect(Collectors.toList());

    assertEquals(namesFlatStream.size(), namesNested.size() * 2);
}
```



# flatMap operation

- a stream can hold complex data structures like `Stream<List<String>>`
- `flatMap()` helps to flatten the data structure to simplify further operations
- in the example:
  - we converted the `Stream<List<String>>` to a simple `Stream<String>`

# peek operation

```
@Test
public void whenIncrementSalaryUsingPeek_thenApplyNewSalary()
{
    Employee[] arrayOfEmps =
    {
        new Employee(1, "Jeff Bezos", 100000.0),
        new Employee(2, "Bill Gates", 200000.0),
        new Employee(3, "Mark Zuckerberg", 300000.0)
    };

    List<Employee> empList = Arrays.asList(arrayOfEmps);

    empList.stream()
        .peek(e -> e.salaryIncrement(10.0))
        .peek(System.out::println)
        .collect(Collectors.toList());

    assertThat(empList, contains(
        hasProperty("salary", equalTo(110000.0)),
        hasProperty("salary", equalTo(220000.0)),
        hasProperty("salary", equalTo(330000.0))
    ));
}
```

# peek operation

- `forEach` is a terminal operation
- sometimes we need to perform multiple operations on each element before any terminal operation
- `peek()` is useful in such situations
- in the example:
  - the first `peek()` is used to increment the salary of each employee
  - the second `peek()` is used to print the employees
  - finally `collect()` is used as terminal operation

# Cuprins

- 1 Avoiding flow control
- 2 Comprehensions
- 3 Generators
- 4 Dictionaries and sets comprehensions
- 5 Recursion
- 6 Eliminating loops
- 7 Streams
  - Stream creation
  - Stream operations
- 8 Bibliography



# Bibliography

- ① Horia Ciocarlie - The programming language universe, second edition, Timisoara, 2013.
- ② Carlo Ghezzi, Mehdi Jarayeri - Programming Languages, John Wiley, 1987.
- ③ Ellis Horowitz - Fundamentals of programming languages, Computer Science Press, 1984.
- ④ Donald Knuth - The art of computer programming, 2002.
- ⑤ David Merz - Functional programming in Python, 2015.
- ⑥ Eugen Paraschiv - A Guide to Java Streams in Java 8: In-Depth Tutorial With Examples, 2022.

